

# CHEFTOP MIND.Maps™

Cooking trays		Oven code: XEVC	Max Gas Consumption					Max Gas Consumption (kW)					Max Heat Input (kW)					Ignition Heat Input (kW)				
Size	N.		G20 (m³/h)	G25 (m³/h)	G25.1 (m³/h)	G30 (kg/h)	G31 (kg/h)	G20	G25	G25.1	G30	G31	G20	G25	G25.1	G30	G31	G20	G25	G25.1	G30	G31
GN1/1	5	0511-GPR	1.59	1.85	1.84	0.91	1.17	15.0	15.0	15.0	15.0	15.0	11.0	11.0	11.0	12.0	12.0	9.0	9.0	8.0	9.0	9.0
	5	0511-GPL	1.59	1.85	1.84	0.91	1.17	15.0	15.0	15.0	15.0	15.0	11.0	11.0	11.0	12.0	12.0	9.0	9.0	8.0	9.0	9.0
	7	0711-GPR	2.01	2.34	2.33	1.16	1.48	19.0	19.0	19.0	19.0	19.0	13.0	13.0	13.0	14.0	14.0	8.5	8.5	8.5	9.5	9.5
	7	0711-GPL	2.01	2.34	2.33	1.16	1.48	19.0	19.0	19.0	19.0	19.0	13.0	13.0	13.0	14.0	14.0	8.5	8.5	8.5	9.5	9.5
	10	1011-GPR	2.33	2.58	2.70	1.34	1.71	22.0	21.0	22.0	22.0	22.0	16.0	15.0	16.0	18.0	17.0	12.0	11.0	12.0	13.0	13.0
	10	1011-GPL	2.33	2.58	2.70	1.34	1.71	22.0	21.0	22.0	22.0	22.0	16.0	15.0	16.0	18.0	17.0	12.0	11.0	12.0	13.0	13.0
	20	2011-GPR	3.60	4.06	4.05	2.07	2.64	34.0	33.0	33.0	34.0	34.0	23.0	23.0	23.0	26.0	24.0	12.0	12.0	12.0	14.0	13.0
	20	2011-GPL	3.60	4.06	4.05	2.07	2.64	34.0	33.0	33.0	34.0	34.0	23.0	23.0	23.0	26.0	24.0	12.0	12.0	12.0	14.0	13.0
GN2/1	6	0621-GPR	2.54	2.95	2.95	1.52	1.87	24.0	23.0	24.0	25.0	24.0	17.0	17.0	17.0	18.0	17.0	15.0	14.0	14.0	15.0	14.0
	6	0621-GPL	2.54	2.95	2.95	1.52	1.87	24.0	23.0	24.0	25.0	24.0	17.0	17.0	17.0	18.0	17.0	15.0	14.0	14.0	15.0	14.0
	10	1021-GPR	3.49	4.06	4.05	2.13	2.72	33.0	33.0	33.0	35.0	35.0	30.0	30.0	30.0	32.0	32.0	13.0	12.0	12.0	16.0	14.0
	10	1021-GPL	3.49	4.06	4.05	2.13	2.72	33.0	33.0	33.0	35.0	35.0	30.0	30.0	30.0	32.0	32.0	13.0	12.0	12.0	16.0	14.0
	20	2021-GPR	7.20	8.12	8.11	4.27	5.44	68.0	66.0	66.0	70.0	70.0	47.0	47.0	47.0	55.0	53.0	22.0	22.0	22.0	26.0	26.0
	20	2021-GPL	7.20	8.12	8.11	4.27	5.44	68.0	66.0	66.0	70.0	70.0	47.0	47.0	47.0	55.0	53.0	22.0	22.0	22.0	26.0	26.0

CHEFTOP MIND.Maps™ XEVC		Cooking trays		Size	GNI/1					
					N.	5 cooking trays		7 cooking trays		10 cooking trays
		Oven code: XEVC		0511-GPR		0511-GPL	0711-GPR	0711-GPL	1011-GPR	1011-GPL
Power	for air heating <sup>o</sup>		kW	15	15	19	19	22	22	
	for steam generation <sup>o</sup>		kW	15	15	19	19	22	22	
Sizes	Width		mm	750	750	750	750	750	750	
	depth		mm	773	733	733	733	733	733	
	Height		mm	675	675	843	843	1010	1010	
Weight	Gross		kg	100	100	115	115	125	125	
	net		kg	85	85	100	100	110	110	
Thermal load	sensible		kW	0.9	0.9	1.0	1.0	1.2	1.2	
	latent	with hood <sup>o</sup>	kW	0	0	0	0	0	0	
		without hood	kW	3.6	3.6	5.1	5.1	7.3	7.3	
Max food load			kg	25	25	35	35	45	45	
IPX_ <sup>o</sup>				IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	
220 - 240 V/ 1PH+N /50Hz	Absorbed power		kW	0.6	0.6	1	1	1	1	
	Absorbed current		A	2.2	2.2	3.5	3.5	3.5	3.5	
	Power cable H07RN-F	Cross-section	mm <sup>2</sup>	1.5	1.5	1.5	1.5	1.5	1.5	
		Length	m	2	2	2	2	2	2	
		Schuko plug		Supplied						
Fuses <sup>o</sup> (number of fuses = 2)		A	16	16	16	16	16	16		
220-240V/ 3PH /50Hz	Absorbed power		kW	not available						
	Absorbed current		A							
	Power cable H07RN-F	Cross-section	mm <sup>2</sup>							
		Length	m							
	Fuses <sup>o</sup> (number of fuses = 3)		A							
380-415V/ 3PH+N /50Hz	Absorbed power		kW	not available						
	absorbed current		A							
	Power cable H07RN-F	Cross-section	mm <sup>2</sup>							
		Length	m							
	Fuses <sup>o</sup> (number of fuses = 3)		A							
AVERAGE CONSUMPTION <sup>o</sup>	Water	for steam generation	l/h	10.7	10.7	13.7	13.7	15.6	15.6	
	Power	for steam generation	kW	10.6	10.6	13.5	13.5	15.4	15.4	